

Pressure Washer Trailers

Single Axle Hot Water



95007

Features

Pump

- GENERAL PUMP® or COMET® triplex plunger pumps
- Pressure safety relief valve
- Ceramic pistons

Engine

- VANGUARD™ or HONDA® brand

Burner System

- 12 volt diesel fired burner system
- Clean burning, fuel efficient combustion chamber
- Utilizes kerosene or #2 diesel fuel
- Burner system provides 120 degree heat rise
- 190 Degree High-limit switch
- On/off switch mounted away from water inlet or outlet

Frame

- 2000lb. single axle construction
- Welded construction
- Box steel powder coated
- Steel fender composition
- Removable tongue jack for easy storage
- 2" ball coupling

Units Include

- 100' high pressure hose reel
- Low pressure hose reel and 3/4" x 75' hose
- High pressure hose, trigger gun and wand
- Four mounting points for nozzles
- Large capacity water tank with steel straps

Model#	PSI	GPM	Engine	Pump	Trailer Size	DOT Lighting	Wheels	High Pressure Hose	Low Pressure Hose	Battery	Water Tank Size
95005	4000	3.5	HONDA® GX390 Electric Start Engine with Oil Aler®	COMET™ Triplex	4' x 5.5' Platform	LED	13"	100' x 3/8" Armor™	3/4" x 75'	12 Volt	200 Gallon w/ Steel Straps & Drain Petcock
95006	4000	3.5	VANGUARD® V-Twin Electric Start with Low Oil Shutdown	COMET™ Triplex	4' x 5.5' Platform	LED	13"	100' x 3/8" Armor™	3/4" x 75'	12 Volt	200 Gallon w/ Steel Straps & Drain Petcock
95007	4000	4.0	VANGUARD® V-Twin Electric Start with Low Oil Shutdown	GP™ Triplex	4' x 5.5' Platform	LED	13"	100' x 3/8" Armor™	3/4" x 75'	12 Volt	200 Gallon w/ Steel Straps & Drain Petcock